

Microservices/serverless, AWS Lambda example

AWS Lambda is a core component for building serverless microservices, allowing you to run code without managing servers. The most common example of this architecture involves **combining Amazon API Gateway with AWS Lambda and Amazon DynamoDB to create a fully serverless, event-driven API.**

Serverless Microservice Architecture Example (API-driven)

This pattern is ideal for creating discrete, independent services that handle specific tasks over HTTP requests, such as processing payments or managing user data.

Key Components

Amazon API Gateway: Acts as the "front door" for the microservice, handling API calls (e.g., GET, POST) and routing them to the appropriate backend service.

AWS Lambda: The compute service that runs your business logic in response to events (in this case, an API request). You only pay for the exact compute time consumed.

Amazon DynamoDB: A serverless NoSQL database used to store and retrieve data for the microservice.

Example Scenario: "Order Processing" Microservice

Imagine a large e-commerce application that needs a dedicated service for handling new orders.

1. The Request:

A user clicks "Place Order" on the website. A front-end application makes a `POST` request to the `/orders` endpoint exposed by the Amazon API Gateway.

2. Event Trigger & Compute:

API Gateway receives the request.

It is configured to trigger a specific AWS Lambda function (e.g., `processOrderFunction`).

AWS Lambda automatically runs the associated code without you needing to provision or manage any server infrastructure.

3. Business Logic & Data Storage:

The `processOrderFunction` executes the order processing logic (e.g., validating items, calculating the total).

The function then writes the new order details into a dedicated `OrdersTable` in Amazon DynamoDB.

4. The Response:

DynamoDB confirms the write operation to the Lambda function.

The Lambda function returns a success response to API Gateway.

API Gateway sends an `HTTP 200 OK` status back to the user's front-end application.

Other Serverless Patterns

Beyond API-driven microservices, AWS Lambda is central to other event-driven patterns:

Data Processing Pipeline: An object uploaded to an Amazon S3 bucket can trigger a Lambda function to resize an image, convert a file, or analyze metadata.

Stream Processing: Data flowing through Amazon Kinesis or Amazon SQS (Simple Queue Service) can trigger Lambda functions for real-time analytics or decoupled message processing.

Revision #2

Created 29 October 2025 02:43:40 by AI API

Updated 11 December 2025 07:11:47 by AI Channel